

www.graco.be

# MARK V<sup>™</sup> ProConnect<sup>™</sup>

For paints, fire retardant and airless plastering applications



# PROFESSIONAL ADVANTAGES

FAST: sprays plasters like

paint at the speed

of airless

CLEAN: hardly no projection

of material

SIMPLE: cleans quickly

and automatically

# **MATERIALS**

Latex

**Emulsions** 

**Acrylics** 

**Epoxies** 

Blockfillers

Fire retardant

Light plasters



MARK V™ ProConnect



Unscrew paint line



Open latch that opens front cover



Remove pin Pump lower is free.

# MARK V<sup>™</sup> ProConnect<sup>™</sup>

# Mark V ProConnect for paints, fire retardant and Airless Plastering Applications



Auto Clean

Easy Out™ Filter system



TiltBack™ leg Easy bucket

change, cleaning and maintenance



Lowered inlet check Improved material suction without cavitation Ceramic balls: high resistance against wear



Big pneumatic wheels Rolls easily over rough terrain and stairs Inner tube facilitates repair



**EXCLUSIVE PUMP ATTACHMENT** Remove and replace your entire pump lower: On the job - without any tools - in seconds

# MARK V™ ProConnect™ **SPECIFICATIONS**

Dart Numberer



# Mark V ProConnect

for Italy, Denmark, Switzerland - 220 V for UK - 110 V  249906  Max. tip size  with paint: 0.035"  Flow - I/min. (gpm)  with plaster: 0.037"  Flow - I/min. (gpm)  with plaster: *up to 5.5 (up to 1.45)  Max. pressure - bar (PSI)	Part numbers:	
for UK - 110 V       249906         Max. tip size       with paint: 0.035" with plaster: 0.037"         Flow - I/min. (gpm)       with plaster: *up to 5.5 (up to 1.45)         Max. pressure - bar (PSI)       230 (3300)         Weight - kgs (lbs)       59 (130)         SmartControl™ version       2.0         Motor type       DC "brushless" TEFC         Motor rating - kW (HP)       1.65 (2.2)	for Europe - 220 V	249905
Max. tip size       with paint: 0.035" with plaster: 0.037"         Flow - I/min. (gpm)       with plaster: *up to 5.5 (up to 1.45)         Max. pressure - bar (PSI)       230 (3300)         Weight - kgs (lbs)       59 (130)         SmartControl™ version       2.0         Motor type       DC "brushless" TEFC         Motor rating - kW (HP)       1.65 (2.2)	for Italy, Denmark, Switzerland - 220 V	249907
with plaster: 0.037"         Flow - I/min. (gpm)       with plaster: *up to 5.5 (up to 1.45)         Max. pressure - bar (PSI)       230 (3300)         Weight - kgs (lbs)       59 (130)         SmartControl™ version       2.0         Motor type       DC "brushless" TEFC         Motor rating - kW (HP)       1.65 (2.2)	for UK - 110 V	249906
Flow - I/min. (gpm)       with paint: 4.3 (1.2) with plaster: *up to 5.5 (up to 1.45)         Max. pressure - bar (PSI)       230 (3300)         Weight - kgs (lbs)       59 (130)         SmartControl™ version       2.0         Motor type       DC "brushless" TEFC         Motor rating - kW (HP)       1.65 (2.2)	Max. tip size	with paint: 0.035"
with plaster: *up to 5.5 (up to 1.45)         Max. pressure - bar (PSI)       230 (3300)         Weight - kgs (lbs)       59 (130)         SmartControl™ version       2.0         Motor type       DC "brushless" TEFC         Motor rating - kW (HP)       1.65 (2.2)		with plaster: 0.037"
Max. pressure - bar (PSI)       230 (3300)         Weight - kgs (lbs)       59 (130)         SmartControl™ version       2.0         Motor type       DC "brushless" TEFC         Motor rating - kW (HP)       1.65 (2.2)	Flow - I/min. (gpm)	with paint: 4.3 (1.2)
Weight - kgs (lbs)         59 (130)           SmartControl™ version         2.0           Motor type         DC "brushless" TEFC           Motor rating - kW (HP)         1.65 (2.2)		with plaster: *up to 5.5 (up to 1.45)
SmartControl™ version2.0Motor typeDC "brushless" TEFCMotor rating - kW (HP)1.65 (2.2)	Max. pressure - bar (PSI)	230 (3300)
SmartControl™ version 2.0 Motor type DC "brushless" TEFC Motor rating - kW (HP) 1.65 (2.2)	Weight - kgs (lbs)	59 (130)
Motor rating - kW (HP) 1.65 (2.2)	SmartControl™ version	
	Motor type	DC "brushless" TEFC
Generator requirements - kW (HP) W 5 (6.7) 5000	Motor rating - kW (HP)	1.65 (2.2)
	Generator requirements - kW (HP) W	5 (6.7) 5000

<sup>\*</sup> Flow rates vary with different plasters. Smaller ID ceramic balls provide higher flow with plaster than SST balls with paint.

The Mark V™ Pro-Connect ships complete and ready to spray! Accessory Box standard: 241705 Blue Texture Gun, GHD631 HD Reversible Tip and Guard, 240797 BlueMax™ II hose 3/8" x 15 m, 244926 BlueMax™ II Whip Hose 1/4" x 0.9 m,159841 1/4" x 3/8" Adapter, 189018 Gun Swivel, 206994 TSL™ 0.25 I, 222297 Angle Adapter (outlet fitting when using Hopper), Set of SST Balls and Seats for paint spraying, 111733 adjustable wrench and 197193 universal hammer tool.

# **ACCESSORIES**

#### Gun

241705 TexSpray<sup>™</sup> blue gun with GHD631 and GHD guard

# Easy Out™ Pump Filters

244071 30 mesh, grey 244067 60 mesh, black 244068 100 mesh, blue 244069 200 mesh, red

#### Inlet Strainer Ultra® Max II

189920 metal

**Hoses (230 bar)** 240797 3/8" x 15 m 241274 3/8" x 20 m 241275 3/8" x 30 m

# Whips (230 bar)

238358 3/16" x 0.9 m 3/16" x 1.4 m 238959 238359 3/16" x 1.8 m

244926 BlueMax™ II whip hose 1/4" x 0.9 m

#### **Adapters**

159841 1/4"(F) x 3/8"(M) adapter 189018 Gun swivel

## **TexSpray kits** = Texture gun, 3/8" hose, whip, GHD 631 tip

241338 230 bar

244925 280 bar

# **Pump Lower**

287928

## **Hopper** 241318 90 liter hopper kit

248531 Bag roller kit 243428 Wheel kit for hopper

#### Atomizer kit

244052 Air atomizer kit with hose

# Flexible suction kits

243167 Container suction kit

## **PRO Tip Extensions**

with RAC®X Guard 287019 25 cm 287020 40 cm 287021 50 cm 287022 75 cm

# CleanShot™ Pole Gun

287026 90 cm w/ RAC®X 287027 180 cm w/ RAC®X

#### **Tips**

GHDXXX GHD tips

RAC® X long life tips LTXXXX TMXXXX Plaster reversible tips WRXXXX RAC®X WideRac tip

# **Guards**

222674 GHD™ guard 243161 RAC® 5 guard 246215 RAC® X guard

# Liquids

206994 TSL™ 0.25I 243103 Pump Armor™ 1I 245133 Pump Armor 3.8 I